

The Dishwashing Machine Specialists

QTY:
SIS #

# 64 PRO w/ Heat Recovery Electric

# HIGH TEMPERATURE 2-TANK ELECTRIC RACK CONVEYOR



Rendered image is for general visual representation only. Please refer to specifications for the latest detailed product information.

Customers save \$1500 per year in energy cost on average when compared to a standard machine!

### STANDARD FEATURES

- **Exhaust Air Energy Recovery** reuses waste energy to preheat incoming water
- Perpetual Rack Advance System with digital jam monitoring, and mechanical drive protection
- **Automated Delime Function** with user-customizable alert intervals
- 348 Racks Per Hour
- .28 Gallons/Rack With Energy Sentinel (idle pump shut-off)
- **Advanced Touchscreen Display** intuitive condition alerts, with user friendly cleaning and operation visual guidance, multi-lingual
- **Enhanced Visual On-board Diagnostics** quickly identify machine faults for rapid resolution and less
- **Automatic Tank Fill**
- **Programmable Machine Dwell** pauses rack in wash zone for extended cleaning, NSF Certified . Pot & Pan Mode
- **Automatic Drain Valve**
- Single-Piece Hood Design
- Single-Piece Scrap Screen more robust and faster cleaning
- Single-Piece Stainless Steel Upper And Lower Wash Arm
- 20" Standard Vertical Clearance accommodates 18" x 26" sheet pans
- **Fully Insulated Doors** open a full 180° for unrestricted cleaning access
- All Stainless Steel Heavy Gauge Construction including base, legs and feet
- **Enclosure Panels** (front and sides)
- 2 HP Pump Motors with stainless steel impellers
- Factory Authorized Start-Up
- **Vent Fan Control**
- **ENERGY STAR® Certified**









### SPECIFIER STATEMENT

Specified unit will be Champion Model 64 PRO w/Heat Recovery Option (Electric) 2-tank high temperature rack conveyor dishwashing machine. Features top mounted Prodigy HMI user interface controls with proactive maintenance software, proportional rinse, using only 100 GPH, built-in 21 kW booster, progressive anti-jam drive system, energy sentinel (idle pump shut-off), 348 racks per hour, single-piece hood design, single-piece stainless steel upper & lower wash arms manifolds, full 180° opening leak proof insulated hinged access doors.

### 1 Year parts and labor warranty.

R

3765 Champion Blvd. Winston-Salem. NC 27105 Tel: (336) 661-1556 Fax: (336) 661-1979 www.championindustries.com

2674 N. Service Rd., Jordan Station, Ontario, Canada LORISO Tel: (905) 562-4195 Fax: (905) 562-4618 www.championindustries.com/1canada

ev. 09/2025	Printed in U.S.A.	APPROVAL:	DATE:



# 64 PRO w/ Heat Recovery Electric

HIGH TEMPERATURE 2-TANK ELECTRIC RACK CONVEYOR

#### **ACCESSORIES**

- □ Drain water tempering kit (unmounted)
- ☐ Table limit switch, unmounted (recommended on all rack conveyor installations) (unmounted)
  - o WHISKER STYLE
  - o BUTTON STYLE
- Vent cowl, stainless steel with 7" stacks & locking dampers
- ☐ Flanged feet (unmounted)
- □ Water hammer kit (unmounted)
- Chemical pump kit (detergent and rinse aid, mounted and interwired)
- Water pressure regulating valve (unmounted; standard with booster)
- □ ION scale prevention device (unmounted) (HW & CW lines)
- ☐ Water softening system (manufactured, warrantied and serviced by Kinetico)
- □ Dish racks:
  - o PEG RACK
  - o FLAT RACK
  - o SHEET PAN RACK
- ☐ Splash shields (load end only)
- ☐ Cantilever sideloader (without hood) for 90° load operation
  - o 24" SIDELOAD
  - o 30" SIDELOAD (ACCEPTS SHEET PANS)
- ☐ Model PRO-90B unloader (90° corner conveyor table)
- ☐ Model PRO-90B loader (90° corner conveyor table)
- ☐ Model RCT 64 or RCT 84 roller conveyor table (see factory for custom length)
- ☐ Stainless steel rear enclosure panels
- □ Correctional package (contact factory)

#### **OPTIONS**

- □ 33" Blower dryer electric
- □ Direct link connectivity solution
- ☐ Direct link plus+ connectivity solution

Cantilever Sideloader (no hood)



#### PRO-90B

90° Corner Conveyor table loader and unloader available



**Model RCT 64 or RCT 84** 

Roller conveyor table



In the USA: 3765 Champion Blvd, Winston-Salem, NC 27105 | Tel: (336) 661-1556 Fax: (336) 661-1979 | www.championindustries.com

In Canada: 2674 N. Service Rd., Jordan Station, Ontario, Canada LORISO | Tel: (905) 562-4195 Fax: (905) 562-4618 | www.championindustries.com/lcanada



# 64 PRO w/ Heat Recovery Electric

HIGH TEMPERATURE 2-TANK ELECTRIC RACK CONVEYOR

#### **UTILITIES**

1	Electrical Connections				
	Machine electrical connection and booster electrical connection				
2	Hot Water				
	25 PSI flowing pressure (machine with built-in booster) Main connection 3/4" NPT, 110° incoming water (Initial Fill = 34 Gal)				
3A	Cold Water				
	30 PSI flowing connection 1/2" NPT; 55° Minimum				
5A	Drain				
	Connection 1-1/4" NPT				
	Drain Max Flow Rate (g/min) 15				
8	Vents				
	A Stack connection – load end 200 CFM @ 1/4" static pressure				
	B Stack connection – unload end 200 CFM @ 1/4" static pressure				

**Warning:** Plumbing and electrical connections should be made by qualified personnel who will observe all the applicable plumbing, sanitary, and safety codes and the National Electrical Code.

**Note:** Water Hammer Arrestor (meeting ASSE-1010 standard or equivalent) to be supplied (by others) in common water supply line at service connection.

**Plumbing Notes:** Because of the variation in house-supplied steam and water pressures, steam and water pressure regulating valves (PRVs) may be needed. (Water PRV is standard on machines with booster.) The PRVs can either be purchased from Champion or obtained locally.

Champion does not endorse using on-demand (tankless) water heating systems, as well as PEX and other plumbing materials that may limit water flow, as these could impair machine performance. For optimal results, we recommend using appropriately sized conventional hot water tanks and standard copper water supply lines that adhere to our specifications. Not following these recommendations may void the manufacturer's warranty.

Water hardness of 3 grains/US Gal (0.83 Imp Gal) - 5.3 Mg/L or less

Venting Notes: Fabricated duct size: 3-7/8" x 15-7/8" (outside dimensions)

**Note:** Freezing air must not be allowed to be drawn down into the heat recovery coil when building vent fan is off if direct vent ducting is connected to the machine.

Optional Drain Tempering: 1/2" NPT cold water connection required. 1/2" NPT drain connection from back flow preventer to house drain. (FIELD INSTALLED and PLUMBED).

#### **SPECIFICATIONS**

Capacity	
Racks per hr (NSF rated)	348
Wash tank (US gal.)	17
Power rinse tank (US gal.)	17
Conveyor speed (ft/min)	9.6
Conveyor speed Pot/Pan Mode (ft/min) (only one rack at a time in pot/pan)	4.6
Motor Horsepower	
Drive	1/6
Wash	2
Power Rinse	2
Water Consumption	
US Gal. per hr (max. use)	100
US Gal. per rack	.28
Heating	
Tank heat, electric (kW)	15
Power Rinse, electric (kW)	10
Electric booster (built-in) (kW supplied for 70° F rise)	21
Booster heaters completely inter plumbed, controls are inte	rwired.
Venting	
Load end (minimum CFM)	200
Unload end (minimum CFM)	200
Standard 20"x 20" Rack Complement	
Peg	1
Flat	1

## Two Tank PRO Rack Machine and Booster Ratings

The tables below give the ratings for each model. The ratings include the requirements of the 21 kW booster heater.

#### Machines with a Single point electrical connection:

64 PRO HR Electric, Tank Heat, 21 kW 70° Booster				
Elec. Specs	Rated Amps	Minimum Supply Ckt. Conductor Ampacity	Maximum Overcurrent Protective Device	
208/60/3	Call factory for this special engineering option			
240/60/3	131	175	175	
480/60/3	66	90	90	
575/60/3	53	70	70	

#### Machines with a Dual point electrical connection:

64 PRO HR Electric, 21 kW Booster Only				
Elec. Specs	Rated Amps	Minimum Supply Ckt. Conductor Ampacity	Maximum Overcurrent Protective Device	
208/60/3	59	80	80	
240/60/3	51	70	70	
480/60/3	26	35	35	
575/60/3	22	30	30	

64 PRO HR Electric, Machine Only				
Elec. Specs	Rated Amps	Minimum Supply Ckt. Conductor Ampacity	Maximum Overcurrent Protective Device	
208/60/3	90	110	110	
240/60/3	80	100	100	
480/60/3	40	50	50	
575/60/3	31	40	40	

#### Note:

Machine ships as a dual point electrical connection standard. Easily converted to a single point connection by a qualified electrician (except as show in above tables).

In the USA: 3765 Champion Blvd, Winston-Salem, NC 27105 | Tel: (336) 661-1556 Fax: (336) 661-1979 | www.championindustries.com

In Canada: 2674 N. Service Rd., Jordan Station, Ontario, Canada LORISO | Tel: (905) 562-4195 Fax: (905) 562-4618 | www.championindustries.com/lcanada




# 64 PRO w/ Heat Recovery Electric


HIGH TEMPERATURE 2-TANK ELECTRIC RACK CONVEYOR

Shipping weight crated: 865 lbs. Dimensions shown in inches


# 




### Plan View: Left to Right Model




# Plan View: Right to Left Model R-1



#### **End View**







Suggested Table Construction

Flange Details

In the USA: 3765 Champion Blvd, Winston-Salem, NC 27105 | Tel: (336) 661-1556 Fax: (336) 661-1979 | www.championindustries.com

In Canada: 2674 N. Service Rd., Jordan Station, Ontario, Canada LORISO | Tel: (905) 562-4195 Fax: (905) 562-4618 | www.championindustries.com/lcanada

Rev. 09/2025 Printed in U.S.A.

Due to an ongoing value analysis program at Champion, specifications contained in this catalog are subject to change without notice.

